Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claims 1 - 18 (cancelled)

Claim 19 (currently amended): A method of treating and reactivating a sorbent for use in capturing carbon dioxide in a fuel combustion process, wherein the combustion process is performed in a fluidized bed and generates carbon dioxide, and the sorbent comprises a calcinable alkaline earth metal, the method comprising

- (a) calcining the sorbent to form an alkaline earth metal oxide; and thereafter
- (b) introducing the alkaline earth metal oxide into a carbonator at a <u>high</u> temperature of at least 700°C, and subjecting sufficient to react the alkaline earth metal oxide to <u>with a</u> concentrated stream of carbon dioxide <u>capable of shocking the sorbent of a concentration of at least 85%</u> to produce a carbonate of the alkaline earth metal;
 - (c) transferring the alkaline earth metal carbonate into the fluidized bed;
- (d) calcining the alkaline earth metal carbonate to regenerate the alkaline earth metal oxide and carbon dioxide;
 - (e) selectively removing the carbon dioxide produced in step (d); and
- (f) returning the alkaline earth metal oxide product of step (d) to the carbonator to capture carbon dioxide generated in the fuel combustion process; and thereafter
 - (g) repeating steps (c) to (f) and selectively repeating step (b) between steps (f) and (c).

Claim 20 (previously presented): The method as defined in claim 1, wherein the carbon dioxide produced in step (d) is pure carbon dioxide.

Claim 21 (previously presented): The method as defined in claim 19, wherein step (b) further produces a residue comprising at least one of spent sorbent material and surplus carbon dioxide,

Appl. No. 10/577,542

Amdt. Dated Jan. 6, 2010

Reply to Office Action of Oct. 6, 2009

and step (b) further comprises recovering the residue.

Claim 22 (previously presented): The method as defined in claim 19, wherein the alkaline earth

metal carbonate is limestone.

Claim 23 (previously presented): The method as defined in claim 19, wherein the alkaline earth

metal oxide is lime.

Claim 24 (previously presented): The method as defined in claim 19, wherein the fluidized bed

comprises a pressurized fluidized bed combustor (PFBC/C).

Claim 25 (previously presented): The method as defined in claim 19, wherein the fluidized bed

comprises a circulating fluidized bed combustor (CFBC/C).

Claim 26 (currently amended): A method of treating and reactivating a sorbent for use in

capturing carbon dioxide in a fuel combustion process, wherein the combustion process is

performed in a fluidized bed and generates carbon dioxide, and the sorbent comprises a

calcinable alkaline earth metal, the method comprising

(a) calcining the sorbent in a first calciner to form an alkaline earth metal oxide;

(b) treating the alkaline earth metal oxide in a hydration reactor to form an alkaline earth

metal hydroxide;

(c) carbonating the alkaline earth metal hydroxide at a high temperature of at least 700°C

and subjecting sufficient to react the alkaline earth metal hydroxide to with a concentrated stream

of carbon dioxide of a concentration of at least 85% capable of shocking the sorbent to produce a

carbonate of the alkaline earth metal and water;

(d) transferring the alkaline earth metal carbonate into a second calciner and calcining the

alkaline earth metal carbonate to regenerate the alkaline earth metal oxide and produce carbon

dioxide;

Page 3 of 7

Appl. No. 10/577,542

Amdt. Dated Jan. 6, 2010

Reply to Office Action of Oct. 6, 2009

(e) introducing the alkaline earth metal oxide into a carbonator at a temperature of at least

600°C and subjecting the alkaline earth metal oxide to carbon dioxide of a concentration of at

least 85% to produce a carbonate of the alkaline earth metal;

(f) selectively removing the carbon dioxide produced in step (d);

(g) returning the alkaline earth metal oxide product of step (d) to the carbonator to

capture carbon dioxide generated in the fuel combustion process; and thereafter

(h) repeating steps (b), (c), (d), (f) and (g), and selectively repeating step (e) between

steps (f) and (g).

Claim 27 (previously presented): The method as defined in claim 26, wherein step (e) further

produces a residue comprising at least one of spent sorbent material and surplus carbon dioxide,

and step (e) further comprises recovering the residue.

Claim 28 (previously presented): The method as defined in claim 26, wherein the carbon dioxide

produced in step (d) is pure carbon dioxide.

Claim 29 (previously presented): The method as defined in claim 26, wherein step (b) is

performed using liquid water or steam at a temperature greater than 50°C.

Claim 30 (previously presented): The method as defined in claim 26, wherein step (c) and step

(e) are each performed at a temperature in the range of 700°C to 1200°C.

Claim 31 (previously presented): The method as defined in claim 29, wherein step (b) is

performed at atmospheric pressure.

Claim 32 (previously presented): The method as defined in claim 29, wherein step (b) is

performed at a pressure greater than atmospheric pressure.

Page 4 of 7

Claim 33 (previously presented): The method as defined in claim 26 wherein the alkaline earth metal carbonate is limestone.

Claim 34 (previously presented): The method as defined in claim 26, wherein the alkaline earth metal oxide is lime.

Claim 35 (previously presented): The method as defined in claim 26, wherein the fluidized bed comprises a pressurized fluidized bed combustor (PFBC/C).

Claim 36 (previously presented): The method as defined in claim 26, wherein the fluidized bed comprises a circulating fluidized bed combustor (CFBC/C).